



DECLARATION OF PERFORMANCE

Nº 005KKNE2017

GRES ARAGÓN

1. Unique identification code of the product type

Type, batch or serial Lumber or any other element allowing identification of the product

Extruded ceramic tiles, with water absorption $3% < E_b \leq 6%$ type 5*

2. Intended use(s)

For internal and external walls and floorings

3. Name or registered trade mark, and contact address of the manufacturer

Gres de Aragón, S.A.

Carretera Escatrón Km.9 44600 ALCAÑIZ (TERUEL) ESPAÑA

4. System(s) of assessment and verification of constancy of performance (AVCP)

System 4

5. Name and identification number of notified laboratory, if relevant

6. Declared performances

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	A1	EN 14411:2016
Breaking strength	> 950 N	
Slipperiness, as:	Rd>45	
Pendulum UNE:ENV:12633:2003 Annex A	Class 3	
Tactility	NPD	
Bond strength/adhesion, for:	>1 N/mm ²	
Cementitious adhesive, type C2		
Thermal shock resistance	Pass	
Durability for::		
- internal use:	Pass	
- external use: freeze-thaw resistance	Pass	

The performance of the product identified in point 1 is in conformity with the declared performances in point 6.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

José Ramón Hernando Encuentra
Gres de Aragón S.A. Representative



Alcañiz, 6th February 2017

(*)Type 5 corresponds to Natural, Natural Classic (Valle, Arán and Aneto), Cotto, Quarry, Glazed Classic Malta, Traffic, Jasper , Retro Natural and Orion series